IN THE CLAIMS:

(Currently Amended) An image pickup apparatus comprising:
 an image pickup element having a color coding filter;

a preprocessing circuit comprising (i) means for generating signals based on output from each line in the image pickup element and for outputting the same; (ii) spatial phase synchronization means for synchronizing horizontal and vertical spatial phases based on the output from each line in the image pickup element; and (iii) synthesis means for generating a synthesized signal based on a signal whose horizontal and vertical spatial phases are synchronized in the spatial phase synchronization means, wherein a signal from the synthesis means is subject to chromaticness processing:

a brightness processing circuit which receives the outputted signals from the generating means and performs brightness processing thereon; and

a chromatic processing circuit which receives the synthesized signal from the synthesis means and performs color processing thereon.

- (Original) An image pickup apparatus according to claim 1,
 wherein the color coding filter is a complementary mosaic color coding filter.
- (Original) An image pickup apparatus according to claim 2,
 wherein the complementary mosaic color coding filter is based on a repetition
 of two pixels horizontally by four lines vertically, and

wherein the filter comprises:

a first line which is an alternate repetition of Cy (cyan) and Ye (yellow);

-2- 00222621

a second line which is an alternate repetition of G (green) and Mg (magenta);

- a third line which is an alternate repetition of Cy and Ye; and
- a fourth line which is an alternate repetition of Mg and G.
- 4. (Original) An image pickup apparatus according to claim 2, wherein the synthesis means generates new signals S1r, S2r, S1b, and S2b by performing the following operations:

$$S1r = Cy + G$$
, $S2r = Ye + Mg$

$$S1b = Cy + Mg$$
, $S2b = Ye + G$

based on Cy (cyan), Ye (yellow), G (green), and Mg (magenta) of each pixel data in a signal whose horizontal and vertical spatial phases are synchronized in the spatial phase synchronization means.

- 5. (Original) An image pickup apparatus according to claim 1, wherein the image pickup element is read on a frame basis by independently scanning odd-numbered and even-numbered lines.
- 6. (Currently Amended) An image pickup method for an image pickup apparatus provided with an image pickup element having a color coding filter, wherein the image pickup method comprises:

the step of generating output signals by use of a generating means based on output from each line in the image pickup element and outputting the same;

the step of allowing spatial phase synchronization means to synchronize horizontal and

-3- 00222621

vertical spatial phases based on the output from each line in the image pickup element;

the step of allowing synthesis means to create a synthesized signal based on a signal whose horizontal and vertical spatial phases are synchronized in the spatial phase synchronization means;

the step of performing brightness processing on the outputted signal obtained from the generating means; and

the step of performing chromaticness processing for a signal from the synthesis means.

- 7. (Original) An image pickup method according to claim 6, wherein the color coding filter is a complementary mosaic color coding filter.
- 8. (Original) An image pickup method according to claim 7,

wherein the complementary mosaic color coding filter is based on a repetition of two pixels horizontally by four lines vertically, and

wherein the filter comprises:

- a first line which is an alternate repetition of Cy (cyan) and Ye (yellow);
- a second line which is an alternate repetition of G (green) and Mg (magenta);
- a third line which is an alternate repetition of Cy and Ye; and
- a fourth line which is an alternate repetition of Mg and G.
- 9. (Original) An image pickup method according to claim 7, wherein the synthesis means generates new signals S1r, S2r, S1b, and S2b by

-4- 00222621

performing the following operations:

$$S1r = Cy + G$$
, $S2r = Ye + Mg$

$$S1b = Cy + Mg$$
, $S2b = Ye + G$

based on Cy (cyan), Ye (yellow), G (green), and Mg (magenta) of each pixel data in a signal whose horizontal and vertical spatial phases are synchronized in the spatial phase synchronization means.

10. (Original) An image pickup method according to claim 6,

wherein the image pickup element is read on a frame basis by independently scanning odd-numbered and even-numbered lines.

-5- 00222621